



Lenox Instrument Company, Inc.
265 Andrews Road • Trevose, PA 19053
USA 800-356-1104 • Worldwide 215-322-9990
Fax 215-322-6126 • sales@lenoxinst.com

Lenox / Pultz Cameras For The Glass Industry



- **Rugged Reliability**
- **Clear Sharp Images**
- **Long-Lasting Performance**
- **Economical**

The **Lenox / Pultz** family of high-temperature video camera systems are designed to be mounted directly through the wall of a glass furnace or flush with the exterior wall. The stainless steel camera housing employs a steel triple-wall laminar flow for efficient water-cooling of the camera and pinhole lens technology to provide clear, real time high-resolution images, enabling operation in hostile environments up to 4250°F (2345°C). An Aluminum water-cooled camera housing enables operation in environments up to 500°F (260°C) with pin hole or 300°F (149°C) with window and are ideal for hot area monitoring.

Applications include the optimization of burner flame geometry, monitoring of material mix, melting point, bubbler operation, batch pile and formation patterns and refractory wear. Water-cooled aluminum camera housing models have been used to monitor windscreen bending operations, helping reduce the number of breakages and improving overall efficiency.

Backed by the expertise and know-how of one of the most trusted names in the field.



Lenox Instrument Company, Inc.
 265 Andrews Road • Treose, PA 19053
 USA 800-356-1104 • Worldwide 215-322-9990
 Fax 215-322-6126 • sales@lenoxinst.com

Product Specifications

Stainless Steel Camera Enclosure		Aluminum Camera Enclosure
1/3" CCD Color Camera	Camera Type	1/3" CCD Color Camera
Water-cooled 304 Stainless Steel	Construction	Water-cooled aluminum enclosure with or without air purge
4250°F (2345°C) (Standard with Pinhole)	Max Temperature	300°F (149°C) with window (Standard) 500°F (260°C) with PH (Pinhole)
Straight	Direction of View	Straight
Fixed or 5X Zoom	Field Coverage (see below)	Variable Zoom
18" (457mm), 24" (598mm), 31" (762mm)	Length	17" (432mm)
45lb (21kg), 55lb (25kg) and 67lb (30kg)	Weight	12 lb (5.4kg)
6.4" (162mm)	Diameter	5.5" (139mm)
Good quality, sediment – free water	Cooling Requirements	Good quality, sediment – free water

Model Number Information:

(Example: 6900SC-2406/F0)

6900 SC - 24 0 6 / XX XX
 (Model) (Type) (Length) (Filters) (Lens) (Mounting) (Special)

Enclosure Types: SC = Stainless, AC = Aluminum
Lengths: See Specification Chart Above
Filters: (For all "SC" types and for "AC" with "PH" special
 "0" = None, "1", "2", "3", "4" are Neutral Density, "W" is shade 5 green
Lenses: Select Lens Number from Coverage Chart Below
Mounting: "F0" is standard cradle mount for AC and SC types
 SC options only are: "F1" = 8"-150# flange, "F2" = Flat plate flange
Specials: "EX" for Export (PAL type, 220V, SC and AC type.)
 "PH" = Pinhole modification for AC type.

CAMERA TYPE AND LENS NUMBER AVAILABILITY		
Camera Type	Lens Number	Coverage (Approx)
SC and AC with "PH" Special	3	62°V x 78°H x 95°D
	4	45°V x 60°H x 72°D
	6	34°V x 44°H x 55°D
	Z	45°V x 60°H x 72°D to 9°V x 12°H x 15°D
AC only	V	62°V x 78°H x 95°D to 26°V x 34°H x 43°D